

## Claims

1. A user interface device for electronic apparatus, the device comprising a keypad having a plurality of keys each arranged to actuate a respective switch so as to provide a first type of user input and integrally disposed impedance sensor so as to provide a second type of user input.
2. A device according to claim 1, wherein the keypad includes a region provided with said impedance sensor but without a key.
3. A device according to claim 1, wherein said keys are comprised in a keymat.
- 10 4. A device according to claim 3, wherein the impedance sensor is disposed adjacently to the keymat.
5. A device according to claim 3, wherein the keymat and the impedance sensor are coextensive.
6. A device according to claim 1, wherein the keys comprise silicone rubber.
- 15 7. A device according to claim 1, wherein the keys include a hard coat.
8. A device according to claim 1, wherein the impedance sensor is arranged to detect the presence of a digit.
9. A device according to claim 1, wherein the impedance sensor comprises first and second sensing plates.
- 20 10. A device according to claim 9, wherein the first sensing plate comprises a first set of electrodes.
11. A device according to claim 10, wherein the electrodes are arranged in non-contiguous stripes.

12. A device according to claim 10, wherein the electrodes are transparent.
13. A device according to claim 10, wherein the electrodes are made from indium-tin-oxide.
14. A device according to claim 9, wherein the first sensing plate comprises a substrate.
15. A device according to claim 14, wherein the substrate is substantially transparent.
16. A device according to claim 14, wherein the substrate is made from polyethylene terephthalate.
17. A device according to claim 10, wherein the second sensing plate comprises a second set of electrodes.
18. A device according to claim 17, wherein the first and second set of electrodes are spaced apart.
19. A device according to claim 18, wherein a first member of the first set of electrodes and a first member of the second set of electrodes are arranged to have a mutual capacitance.
20. A device according to claim 19, wherein said members are arranged so to allow the mutual capacitance to change when a digit touches the keypad.
21. A device according to claim 1, wherein the impedance sensor is a capacitive sensor.
22. A device according to claim 1, further comprising a light source to illuminate the keypad.

23. A device according to claim 22, wherein the light source is disposed behind the keys.

24. A device according to claim 22, wherein the light source is planar.

25. A device according to claim 22, wherein the light source is an  
5 electroluminescent layer.

26. A device according to claim 1 wherein the first type of user input is input of alphanumeric data.

27. A device according to claim 1 wherein the second type of user input is control of a focus on a display of the electronic apparatus.

10 28. Electronic apparatus incorporating a device according to claim 1.

29. Electronic apparatus according to claim 28, which is portable.

30. A mobile telephone handset incorporating a device according to claim 1.

31. An electronic communicator handset incorporating a device according to claim 1.

15 32. A portable computer incorporating a device according to claim 1.

33. A method of fabricating a user interface device for electronic apparatus comprising providing a keypad having a plurality of keys each arranged to actuate a respective switch so as to provide a first type of user input and integrally disposing impednace sensor so as to provide a second type of user input.